

Your Information	Step 1: Ship to Information										Step 2: Patient Information								
	Ship to Account:										First Name:								
	Account Name:										Last Name:								
	Address:										Age:								
											Last 4 digits of Social Security #:								
	City:					State:			Zip:		Audiometric Information (required)								
	Phone #:										Hz:	250	500	1k	2k	3k	4k	6k	8k
	Contact Name:										AC Right:								
	Email (required):										AC Left:								
	Bill to Account:																		
Date:					Fitting Date:														

Opn 1* Invisibility Non-Wireless	Style	Battery	L	R	Push button		Volume wheel		Auto Phone		T-Coil/ Auto-Coil		Power (100 dB)		Connectivity Accessories (Bluetooth® required)	
			L	R	L	R	L	R	L	R	L	R	L	R		
IIC	10															-----Not Available-----
CIC	10															-----Not Available-----

Opn 1* NFI Ear to Ear Wireless	Style	Battery	L	R	Push button		Volume wheel		Auto Phone		T-Coil/ Auto-Coil		Power (100 dB)		Connectivity Accessories (Bluetooth® required)	
CIC	10															-----Not Available-----

Opn 1 Bluetooth 2.4 GHz + NFI	ITC**	312															
	HS (half shell)**	312															
		13															
	FS (full shell)**	312															
13																	

- ConnectClip
- Remote Control 3.0
- TV Adapter 3.0
- Phone Adapter 2.0 (ConnectClip required)

For Tinnitus SoundSupport™, a push button and NFI is necessary.
 *Aids without Bluetooth need to be cabled for programming
 **Push button is required to activate Flight Mode

Product Options	Faceplate	Shell Color	Canal Length (Factory select unless marked)	Vent Size (Factory select unless marked)		
	<input type="checkbox"/> Black (IIC Only)	<input type="checkbox"/> Red or Blue	<input type="checkbox"/> As marked	<input type="checkbox"/> Small 1.0	<input type="checkbox"/> No Vent	
	<input type="checkbox"/> Beige	<input type="checkbox"/> Clear	<input type="checkbox"/> Short (before 1 st bend)	<input type="checkbox"/> Medium 1.4	<input type="checkbox"/> Pressure	
	<input type="checkbox"/> Light Brown	<input type="checkbox"/> Beige	<input type="checkbox"/> Medium (at 1 st bend)	<input type="checkbox"/> Large 2.4		
	<input type="checkbox"/> Medium Brown	<input type="checkbox"/> Light Brown	<input type="checkbox"/> Long (before 2 nd bend)	<input type="checkbox"/> Extra Large		
	<input type="checkbox"/> Dark Brown		<input type="checkbox"/> Deep (at 2 nd bend)	<input type="checkbox"/> Largest Possible		

Please Send:

- Return Impressions
- Impression Boxes
- Shipping Bags
- Airbills
- New Cables
- New Flex Strips
- 10 Battery Adapters for programming
- BTE Product Order Forms
- Custom Product Forms
- RITE Mold Forms
- RITE Product Order Forms
- Service Order Forms

Other Options	Retention	Removal	Tactile	Other
	<input type="checkbox"/> Canal Lock	<input type="checkbox"/> Removal Cord (Std IIC/CIC)	<input type="checkbox"/> Raised Push Button	<input type="checkbox"/> Name on Shell (9 characters max.)
	<input type="checkbox"/> Helix Lock			_____
	<input type="checkbox"/> Soft Coat	<input type="checkbox"/> Removal Notch	<input type="checkbox"/> Raised VC Wheel	<input type="checkbox"/> Color Dots
<input type="checkbox"/> Clothing Loop	<input type="checkbox"/> Matte Finish			

Special Instructions:

INTERNAL USE ONLY
DO NOT WRITE

21-137258 15555-10350/03-21

Custom Order Form - Reference Guide

Offering a full range of custom styles and features for Opn 1 there is a custom product for all your patient's needs.

In addition to size and standard custom options, the Velox Custom Portfolio offers wireless and streaming choices – including ear to ear wireless (NFMI) and ear to ear wireless + Bluetooth (2.4 GHz).



How to Choose:

Invisibility

Choose an IIC or CIC for optimal discreetness, offered as Non-Wireless models only.*

(NFMI) Ear to Ear Wireless


Choose a CIC for enabling binaural instrument communication, maximizing Oticon's audiological features.* Wireless programming not available with NFMI only devices.

Bluetooth (2.4 GHz) + NFMI

Choose an ITC, HS, or FS for direct Bluetooth streaming to both ears and binaural instrument communication, fully compatible with all connectivity devices including ConnectClip, Remote Control 3.0, Phone Adapter 2.0, TV Adapter 3.0 and ON app. Free form openings take advantage of space to ensure largest vent possible.

*Connectivity accessories, including Remote Control, and Oticon ON app are not available.

Getting the Fit Right - It Starts with the Impression



Be sure to provide an impression with a full concha and helix area and a canal past the second bend regardless of the model selected.

Vents are calculated in Genie 2 unless otherwise specified in the "Vent Size" or "Special Instruction" section on the order form.

Accessories



T-Cap

The nano-coated, wax-repellent T-Cap filter is used to protect the microphone for all miniature custom styles using size 10 batteries.



O-Cap

The new nano-coated O-Cap microphone protection filter is designed to reject wax and fits all instruments using battery size 312 and 13.



ProWax miniFit

Providing advanced receiver port protection, the ProWax miniFit filter fits all styles in the new Oticon product family.



T-Cap (mic cover)

Gray compact/Black tools

Part Number (1 pc):

123328 - Beige
123330 - Light Brown
123331 - Med Brown
123329 - Dark Brown
123327 - Black



O-Cap (mic cover)

Gray compact/Black tools

Part Number (1 pc):

128003 - Beige
128004 - Light Brown
128005 - Med Brown
128006 - Dark Brown



ProWax miniFit

Gray "turtle"/Black tools

Part Number (1 pc):

128057